

# T-KIT Switchmatic 2

## Presostat electronic

T-Kit Switchmatic 2 este un presostat electronic integrat intr-un racord cu 3 cai cu supapa de sens. Poate controla pornirea si oprirea electropompelor monofazate pana la 3HP(2,2KW). Presiunea de start si de stop pot fi reglate manual cu ajutorul butoanelor de pe panoul de control. Poate functiona ca presostat nc/no.



Aceasta versiune patentata efectueaza protectia totala a pompelor:

- protectie la lipsa apa.
- protectie ampermetrica.
- protectie la fast-cycling (vas de expansiune defect/incorect presurizat).

Dispozitivul are o iesire pentru alarme(led).

### **Caracteristici tehnice:**

- Tensiune de alimentare: 1 x 230V/50Hz.
- Intensitate curent: maxim 16 A.
- Intervalul de reglare Pstart: 0,5-7 bar.
- Interval de reglare Pstop: 1-8 bar.

- Conexiuni:

- ➔ Intrare: 1”M.
- ➔ Iesire: 1”F.
- ➔ Vas expansiune: 1”F.

- Temperatura maxima a mediului: 50°C.
- Temperatura maxima a apei: 40°C.
- Grad de protectie: IP55.
- Functionare P+P.

