

Submersible motor for 4" wet end

Applications

To be assembled on 4" submersible wet end.

Materials

Motor casing and shaft in AISI 304.
O-rings in NBR/EPDM.

Equipment

Cable without plug (see table).
Joint kit according regulation
NEMA MG1-18.388.
External capacitor.

Motor

Asynchronous 2 poles.
IP68 protection.
Class F insulation.
Continuous operation.
Oil cooled motor.
Single phase motor with built-in thermal protection.

Limitations

Maximum water temperature 35 °C.
Maximum submersion 200m.




Features table

Model	I [A]	P1 [kW]	P2		c [μF]	Cos φ _l	η %	I _{arr} [A]	Axial [N]	Cable		Code
	1~230V	1~	[kW]	[HP]						Ø [mm ²]	L [m]	
O4I 075M	4,7	0,97	0,55	0,75	25	0,88	56	16,5	2000	4 x 1,5	1,7	189188
O4I 100M	5,9	1,2	0,75	1	35	0,90	62	18,9	2000	4 x 1,5	1,7	189189
O4I 150M	8,3	1,7	1,1	1,5	40	0,91	65	26,2	2000	4 x 1,5	1,7	189190
O4I 200M	10,7	2,3	1,5	2	60	0,93	66	35	2000	4 x 1,5	1,7	189192
O4I 300M	15,2	3,3	2,2	3	80	0,93	67	47	3000	4 x 1,5	1,7	189191

Model	I [A]		P1 [kW]	P2		Cos φ _l		η %		I [A]		Axial [N]	Cable		Code	
	3~230V	3~400V	3~	[kW]	[HP]	3~230V	3~400V	3~230V	3~400V	3~230V	3~400V		Ø [mm ²]	L [m]	3~230V	3~400V
O4I 075	-	2	0,95	0,55	0,75	-	0,65	-	58	-	8	2000	4 x 1,5	1,7	-	189205
O4I 100	4,5	2,5	1,2	0,75	1	0,68	0,77	62	61	17,1	9,4	2000	4 x 1,5	1,7	189195	189206
O4I 150	6,2	3,4	1,7	1,1	1,5	0,68	0,69	65	68	27,9	15,5	2000	4 x 1,5	1,7	189196	189209
O4I 200	7,9	4,8	2,2	1,5	2	0,68	0,63	69	72	34,7	18	2000	4 x 1,5	1,7	189197	189210
O4I 300	10,9	6,1	3	2,2	3	0,7	0,69	72	74	56,6	34,2	3000	4 x 1,5	1,7	189198	189203
O4I 400	13,6	7,1	4	3	4	0,73	0,84	75	77	77,5	39,5	5000	4 x 2	2,7	189199	189211
O4I 550	17,6	9,2	5,3	4	5,5	0,74	0,83	76	78	95	49,5	5000	4 x 2	2,7	189200	189212
O4I 750	-	11,7	7	5,5	7,5	-	0,86	-	79	-	64	5000	4 x 2	2,7	-	189213

Dimension and weight

Model	A		B		C Ø máx.	Kg	
	1~	3~	1~	3~		1~	3~
O4I 075	331	331	370	370	94	7,2	7,2
O4I 100	356	356	395	395	94	8,5	8,5
O4I 150	386	371	425	410	94	10,2	9,4
O4I 200	436	386	475	425	94	11,7	10,2
O4I 300	505	450	543	488	94	15,1	11,9
O4I 400	-	520	-	558	94	-	16,2
O4I 550	-	610	-	648	94	-	20,1
O4I 750	-	700	-	738	94	-	24,7



Resin joint



Model	Cables [mm ²]	Code
EC 10	up to 4 x 10	103079
EC 25	up to 4 x 25	103080