

**Tabelul pierderilor de sarcina pentru 100m
dintr-o conducta PVC.**

l/min	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	5"	6"	7"	8"
10	8.26	1.974	0.7	0.175									
15	17.57	4.228	1.512	0.385									
20	30.17	7.28	2.604	0.665	0.217								
25	45.15	11.06	3.97	1.029	0.329								
30	64.4	15.61	5.6	1.463	0.462								
35	86.1	20.86	7.56	1.967	0.623	0.217							
40	114.8	26.74	9.66	1.855	0.805	0.28							
50	172.2	40.74	14.77	3.92	1.225	0.427							
60		57.4	21	5.6	1.736	0.602							
70		77	28	7.56	2.331	0.798							
80		98.7	36.05	9.73	3.01	1.022							
90			44.8	12.25	3.78	1.274	0.322						
100			55.3	14.98	4.62	1.554	0.392						
125			84	23.1	7	2.38	0.602						
150				32.9	9.94	3.318	0.847	0.301					
175				44.1	13.3	4.41	1.141	0.399					
200				57.4	17.15	5.67	1.47	0.518					
250				88.2	26.25	8.61	2.24	0.784	0.252				
300					37.1	12.11	3.15	1.106	0.357				
400					64.4	20.65	5.46	1.89	0.623				
500					98	31.36	8.4	2.891	0.952	0.336			
600						44.1	11.83	4.06	1.351	0.476			
700						58.8	15.82	5.46	1.82	0.63			
800						75.6	20.3	7	2.345	0.812	0.301		
900						93.8	25.2	8.75	2.94	1.015	0.378		
1000							31.15	10.64	3.598	1.232	0.462		
1250							47.6	16.1	5.53	1.876	0.7	0.336	
1500							67.2	22.82	7.84	2.639	0.994	0.476	
1750							90.3	30.45	10.5	3.528	1.33	0.637	0.315
2000								39.2	13.58	4.55	1.701	0.826	0.406
2500								59.5	21	6.86	2.625	1.253	0.623
3000								84	29.4	9.66	3.71	1.771	0.875
5000									87.43	28.91	11.718	5.467	2.821

*Valorile sunt exprimate in mca.